



Main benefits

- High accuracy 3D-wind and temperature profiles up to 100 km
- Continuous and unmanned 24/7 operation - day and night
- Additional measurement of aerosols
- Rugged design for high performance in challenging environments
- Extensive software suite for data product generation and fleet management

Key specifications

Measurements	Wind and temperature profiles up to 100 km, density, aerosols
Optical technology	Tunable Alexandrite Laser, non-coherent detection of Mie and Rayleigh scattering as well as resonance fluorescence
Size and weight	1.3 m ³ , < 300 kg
Required infrastructure	Single phase power, network connection

Product description

The Graw lidarCube is the first commercial lidar system capable of wind and temperature profiling throughout the entire atmosphere. The lidarCube's small and rugged design, value for money and comprehensive software suite make it ideal for large synoptic network installations, while its unique capabilities enable researchers as well as space and defence organisations to enhance their atmospheric profiles.

The combination of decades of optical systems development, advanced mechanical design and construction techniques and modern software make the Graw lidarCube an instrument in a league of its own.

Features

Detection technology

The device uses a diode-pumped narrowband alexandrite laser tuneable by means of a second seeder laser, highly complex filter circuits, and a multi-stage detection bank. However, high accuracy can only be achieved through high-precision stabilisation of the alexandrite laser and a precise knowledge of the current filter characteristics. For this reason, continuous reference measurements are carried out in real time, the result of which is incorporated into the control of the laser and the filters, as well as into the mathematical evaluation.

Design and construction

lidarCube outperforms instruments that are several times its size. This is only achievable through sophisticated design and an extensive use of advanced simulations. Our effort has paid off: lidarCube is an instrument built for field use and for unmanned operations with a high degree of protection from extreme wind, rain and temperature shifts.

Management and data retrieval

Sophisticated software supports easy-to-use data. Advanced data processing automatically generates atmospheric profiles as well as the relevant synoptic messages. Additionally, data can be processed individually per the user's needs so that not only wind and temperature, but also lidar-typical data such as turbulence, extinction, and cloud heights can be evaluated. Built as a device for network installations, extensive fleet management software is also available, which makes overseeing a large deployment of units easily manageable.

Synoptic lidar

lidarCube is the first lidar which is suitable for large-scale synoptic installations. Upper air soundings are limited in space and time, and during adverse weather conditions it is difficult to justify where additional observations are useful. A network of lidarCube devices can augment existing instrument setups, eliminating these problems and always providing additional observation data. Rugged design, compact footprint, and minimal maintenance make lidarCube the perfect device for deployment at existing synoptic ground measurement sites.

Unique applications

Special and defence applications can benefit from the availability of high-altitude data which was not readily attainable before. This greatly increases confidence in marginal conditions, potentially avoiding costly delays and cancellations. Research users meanwhile can profit from a far superior instrument in the same form-factor as the small wind-lidars they are accustomed to.

Availability

lidarCube is currently in pre-production and will be available to support select applications in the near future.

Technical data

Temperature	
Range	0-100 km altitude*
Accuracy 0-10 km*	< 0.1 K
Accuracy 10-50 km	< 1 K
Accuracy 50-70 km	< 10 K
Accuracy 80-100 km	< 5 K
Resolution < 1000 m	1 m
Resolution < 5000 m	10 m
Resolution > 5000 m	200 m

Wind	
Range	0-100 km altitude*
Accuracy 0-10 km*	< 0.1 m/s
Accuracy 10-50 km	< 1 m/s
Accuracy 50-70 km	< 10 m/s
Accuracy 80-100 km	< 10 m/s
Resolution < 1000 m	1 m
Resolution < 5000 m	10 m
Resolution > 5000 m	200 m

Air density	
Range	0-100 km altitude*
Accuracy 0-10 km*	< 1 %
Accuracy 10-50 km	< 5 %
Accuracy 50-70 km	< 10 %
Accuracy 80-100 km	< 1 %
Resolution < 1000 m	1 m
Resolution < 5000 m	10 m
Resolution > 5000 m	200 m

Aerosols	
Range	0-80 km altitude*
NLC (noctilucent clouds)	10-10 m ⁻¹ sr ⁻¹ (99% detection probability)
PSC (polar stratospheric clouds)	10-10 m ⁻¹ sr ⁻¹ (99% detection probability)
Background aerosols	accuracy 99.9% (up to 25 km)
Backscattering accuracy	10-11 m ⁻¹ sr ⁻¹

Terrestrial weather	
Accuracy air temperature	0.3 °C (at 20 °C)
Accuracy wind speed	5% (at 10 m/s)
Accuracy wind direction	+/-3° (at 10 m/s)
Accuracy rel. humidity	+/-5% (at 20°C)*

* ranges from 0-5 km and additional RH measurements only available with LidarCube Revision 2.

Visual information of the sky	
Camera specification (color)	Color HD GV-51J1ACP-C-HQ Rev.1.2
Colour space	Bayer RGB
Resolution	2856 x 2848 px, 8.13 megapixel
Framerate stream	15.4 fps
Camera specification (monochrome)	HD Camera GV-51J1ACP-M-GL Rev.1.2
Colour space	Mono
Resolution	2856 x 2848 px, 8.13 megapixel
Framerate	15.4 fps

Environmental conditions	
Operating temperature	-30°C to +50°C
Hurricane proof	up to category 3
Rain proof	up to 40 l /m ² per hour

Electrical	
Power supply	220V / 50 Hz or 110V / 60 Hz
Power consumption	< 1 kW
Interfaces	LAN, WLAN

Dimensions	
Size	100 cm x 100 cm x 130 cm
Weight	< 300 kg

Imprint/Disclaimer

Graw Radiosondes GmbH & Co. KG
 Muggenhofer Str. 95
 90429 Nuremberg
 Germany

Errors and omissions excepted!

This document is copyright protected. Any reproduction of the contents of this document without prior permission of the author is prohibited. All rights reserved.